


FEATURES

- Compatible with both conventional and addressable systems
- Allows siting of fire alarm panel to an alternative location
- Large 21.5" LCD display
- Sleek unobtrusive design
- Displays active fire zones during an alarm condition without user intervention
- User configured media display
- Built-in fault output for monitoring
- Smart power saving mode conserves battery power during a mains failure
- Remote key switch test facility



DESCRIPTION

dynamicZM is a dynamic zone mimic® compatible with a range of fire alarm control panels, both addressable and conventional. Utilising a 21.5" LCD display, during a fire alarm event **dynamicZM** automatically overrides all media and displays an active fire alarm zone plan, clearly identifying the zone or zones in an alarm condition. Where multiple zones are in an alarm condition, the first zone to be activated (or zone of origin) is identified with a flashing zone boundary. For linked or non-fire zones separate images or messages can be displayed.

Upon the clearing of alarm conditions and a successful reset of the fire alarm system, **dynamicZM** will revert to the user's media display schedule. No user intervention is required at the **dynamicZM** location either for displaying fire alarm zones in alarm or resetting the fire alarm system.

A general fault output is provided to monitor **dynamicZM**. Should the data connection be lost between the fire alarm control panel and **dynamicZM**, the data fault message will be displayed, and the fault output activated. A suitable PSU complete with a fault relay should be used with **dynamicZM**. When the PSU fault relay is activated **dynamicZM** will enter power saving mode to preserve operation via batteries only. In this scenario, the general fault output will also be activated.

A test facility is provided to enable the connection of a remote test switch. Activation of a connected test switch displays the fire alarm zone plan to enable a periodic check of its accuracy, without activation of the main fire alarm system. This displays for 90 seconds before automatically reverting to the user's media display schedule.


dynamicZM can be configured on demand by the end user to display their chosen images and silent video media, without the intervention of a fire alarm engineer. Each **dynamicZM** comes with free access to an online media manager dashboard to configure media and schedules ready for local deployment to **dynamicZM** with a mobile device via Wi-Fi.

dynamicZM is flush mounted as standard, offering a sleek and unobtrusive design suitable for numerous applications.

COMPATIBILITY

dynamicZM is compatible with a range of conventional and addressable fire alarm panels from:





EDUCATION

- Fire alarm panel can be located away from public view or interference
- Clear visual fire indication to visitors at reception
- No limit to media updates
- Non-fire zones display their own specific messages

DESCRIPTION

dynamicZM allows for the fire alarm panel to be located away from constant view and possible public interference in educational premises. In the event of a fire alarm activation, **dynamicZM** can automatically display clear information, eliminating any confusion for staff, pupils, or visitors. Fire alarm zones used for non-fire events, such as lockdown, can display specific information tailored for your school or college. With no limit to media updates, your **dynamicZM** can keep up with current notices for parents and pupils.

COMPATIBILITY

dynamicZM is compatible with a range of conventional and addressable fire alarm panels from:

